

POLYETHYLENE TUBING

APPLICATIONS

- For use with point source drip emitters, micro-spray or micro-sprinklers for irrigating ground cover, trees and shrub beds
- Provides flexible and durable header or transition to dripline
- For on-surface or subsurface installations
- Positions on-line emission devices in hard to reach places

FEATURES & BENEFITS

SPEEDS INSTALLATION OF DRIP IRRIGATION SYSTEM

Allows for fast connections and easy layouts.

UV RESISTANT

Withstands heat, direct sun and harsh environments.

MANUFACTURED UNDER STRINGENT QUALITY CONTROLS

Assures highest quality as every coil undergoes a battery of tests and over 30 quality checks.

MADE WITH THE FINEST LOW DENSITY POLYETHYLENE RESIN AVAILABLE

Available in black or bright white.



BLACK POLYETHYLENE
1,000' COIL



BRIGHT WHITE POLYETHYLENE
1,000' COIL



ORDERING INFORMATION

DESCRIPTION	PRESSURE RATING (psi)	COIL LENGTH	MODEL NUMBER
BLACK POLYETHYLENE TUBING			
16MM O.D. (0.520" X 0.620", 0.050" WALL)	70	250'	PE052062-25
		500'	PE052062-05
		1,000'	PE052062-10
½" (0.620" X 0.710", 0.045" WALL)	52	500'	PE062071-05
		1,000'	PE062071-10
½" (0.600" X 0.700", 0.050" WALL)	61	250'	PE060070-25
		500'	PE060070-05
		1,000'	PE060070-10
¾" (0.820" X 0.940", 0.060" WALL)	54	500'	PE082094-05
		1,000'	PE082094-10
1" (1.060" X 1.200", 0.070" WALL)	49	500'	PE106120-05
BRIGHT WHITE POLYETHYLENE TUBING			
16MM O.D. (0.520" X 0.620", 0.050" WALL)	70	500'	PE052062-05BW
		1,000'	PE052062-10BW
½" (0.600" X 0.700", 0.050" WALL)	61	500'	PE060070-05BW
		1,000'	PE060070-10BW
¾" (0.820" X 0.940", 0.060" WALL)	54	500'	PE082094-05BW
1" (1.060" X 1.200", 0.070" WALL)	49	500'	PE106120-05BW