

PRO-HC

Use this rugged, cost effective and professional-grade Wi-Fi controller for residential and light commercial applications.

Try Hydrawise Software today, hardware-free at hydrawise.com

KEY BENEFITS

- Number of stations:
 - 6, 12, or 24 (fixed models)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- 2 sensor inputs available for use with any Clik sensor and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrawise Software
- 2¾" full-color touchscreen display for Wi-Fi setup, zone testing, and offline programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC
- Transformer output (24 VAC): 1 A
- Controller maximum current draw: 0.8 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n 20 MHz
- Supported security protocols: WPA/WPA2 Personal (only) TLS, SSL
- Approvals: IP44 (outdoor), UL, cUL, FCC, CE, RCM, ISED
- Warranty period: 2 years

USER-INSTALLED OPTIONS

- Wireless HC Flow Meter option permits wireless flow monitoring for Hydrawise enabled systems




Pro-HC
(plastic indoor)
Height: 8¼"
Width: 9½"
Depth: 3½"



Pro-HC
(plastic outdoor)
Height: 9"
Width: 10"
Depth: 4"

Compatible with:



HC Flow Meter



Rain-Clik
Sensor



PXSUNC
Accessory
[Visit fxl.com](http://Visitfxl.com)



EPA WaterSense Approved

Recognized as a responsible water-saving tool by the U.S. Environmental Protection Agency

PRO-HC	
Model	Description
PHC-600i	Fixed 6-station, plastic indoor wall mount
PHC-600	Fixed 6-station, plastic outdoor wall mount
PHC-1200i	Fixed 12-station, plastic indoor wall mount
PHC-1200	Fixed 12-station, plastic outdoor wall mount
PHC-2400i	Fixed 24-station, plastic indoor wall mount
PHC-2400	Fixed 24-station, plastic outdoor wall mount