

STRIP PATTERN NOZZLES

Irrigate narrow turf and planter areas accurately with fixed arc Strip Pattern Nozzles.

KEY BENEFITS

- Designed for accurate coverage of strip areas
- Available in a variety of models for unique, rectangular spaces
- Built to last in harsh conditions

OPERATING SPECIFICATIONS

- Recommended operating pressure: 30 PSI
- Pair with Pro-Spray PRS30 pop-up for pressure regulation to 30 PSI
- Warranty period: 2 years



Left Corner Strip
Rectangle: 5' x 15'



Right Corner Strip
Rectangle: 5' x 15'



Side Strip
Rectangle: 5' x 30'



Side Strip
Rectangle: 9' x 18'









Center Strip
Rectangle: 5' x 30'



End Strip
Rectangle: 5' x 15'

STRIP PATTERN NOZZLE PERFORMANCE DATA

Arc	Pressure PSI	Width x Length	Flow GPM
LCS-515 	20	4' x 14'	0.55
	25	5' x 15'	0.60
	30	5' x 15'	0.65
	35	5' x 15'	0.70
	40	5' x 15'	0.75
RCS-515 	20	4' x 14'	0.55
	25	5' x 15'	0.60
	30	5' x 15'	0.65
	35	5' x 15'	0.70
SS-530 	20	4' x 28'	1.10
	25	5' x 30'	1.20
	30	5' x 30'	1.30
	35	5' x 30'	1.40
	40	5' x 30'	1.50
SS-918 	20	8' x 17'	1.45
	25	9' x 18'	1.58
	30	9' x 18'	1.72
	35	9' x 18'	1.88
CS-530 	20	4' x 28'	1.10
	25	5' x 30'	1.20
	30	5' x 30'	1.30
	35	5' x 30'	1.40
	40	5' x 30'	1.50
ES-515 	20	4' x 14'	0.55
	25	5' x 15'	0.60
	30	5' x 15'	0.65
	35	5' x 15'	0.70
	40	5' x 15'	0.75

Bold = Recommended pressure

Notes: To match the precipitation rate of Standard MP Rotator models, use single-row or triangular spacing. To match the MP800, use rectangular spacing.

See precipitation rate calculation.

RCS-515

